

						<p>The maximum mass fraction of hazardous elements designated in the certificate of analysis:</p> <table border="1"> <thead> <tr> <th>Element</th> <th>Mass fraction</th> </tr> </thead> <tbody> <tr> <td>Cd</td> <td>≤ 0.002%</td> </tr> <tr> <td>Be</td> <td>≤ 0.002%</td> </tr> <tr> <td>Pb</td> <td>≤ 0.002%</td> </tr> <tr> <td>Ni</td> <td>≤ 0.01%</td> </tr> </tbody> </table> <p>See CoA, Doc-ID <b>LLxxxx</b></p>	Element	Mass fraction	Cd	≤ 0.002%	Be	≤ 0.002%	Pb	≤ 0.002%	Ni	≤ 0.01%	
Element	Mass fraction																
Cd	≤ 0.002%																
Be	≤ 0.002%																
Pb	≤ 0.002%																
Ni	≤ 0.01%																
Bio-compatibility	5.3	Biocompatibility	Y/A	Assessment acc. particular standards for biocompatibility	ISO zzzzz-1 ISO a2222	<p>The assessment is handled as a separate detached document. See "6 - test Assessment – ProductXYZ", Doc-ID <b>LLxxxx</b></p>	<b>PASS</b>										
Mechanical properties	5.4.1	General: test	Y/A	After <ul style="list-style-type: none"> <li>– test</li> <li>– test2-cooling,</li> <li>– test3,</li> <li>– test4</li> </ul>	ISO aaaa ISO bbbb-1	The acceptance criteria for the mechanical properties have been met for using the material as intended	<b>PASS</b>										
	5.4.2	Proof stress of 0,2 % test (R <sub>p0.2</sub> )	Y/A	<p>≥ 360 MPa (Type 4)</p> <table border="1"> <thead> <tr> <th>Pass</th> <th>Fail</th> </tr> </thead> <tbody> <tr> <td>1st occasion</td> <td>(first lot of 6)</td> </tr> </tbody> </table>	Pass	Fail	1st occasion	(first lot of 6)	ISO zzz ISO yyy-1	<p>1<sup>st</sup> Batch "zz_1_zz" (n=6 samples) R<sub>p0.2</sub> mean =520.0 MPa, stdev = 10.3 MPa</p> <table border="1"> <tr> <td>111</td> <td>222</td> <td>333</td> <td>444</td> <td>555</td> <td>888</td> </tr> </table>	111	222	333	444	555	888	<b>PASS</b>
	Pass	Fail															
	1st occasion	(first lot of 6)															
	111	222	333	444	555	888											
							<b>PASS</b>										
5.4.3	test after test, (test)	Y/A	≥ 2% (Type 4)	ISO eee ISO sss-1			<b>PASS</b>										
						<table border="1"> <tr> <td>8.0</td> <td>8.9</td> <td>12.8</td> <td>6.6</td> <td>6.9</td> <td>8.2</td> </tr> </table>	8.0	8.9	12.8	6.6	6.9	8.2					
8.0	8.9	12.8	6.6	6.9	8.2												
	5.5	test	N/A	N/A for Type 0-4	ISO yyy ISO uuu-1 method	<table border="1"> <tr> <td>229</td> <td>274</td> <td>261</td> <td>230</td> <td></td> <td></td> </tr> </table>	229	274	261	230			<b>PASS</b>				
229	274	261	230														

## History

*Record/document creation: Please delete the template change history.*

Reason for the preparation / revision: test info

Replaces the following documents: V1.0